



単位：mm

呼び	ねじの呼び Rc × Rc' ◇	A ◇	B ◇	L	L <sub>1</sub>	L'	L <sub>1</sub> '	φD <sub>1</sub>	φD <sub>2</sub>	φD <sub>3</sub>	φD <sub>1</sub> '	φD <sub>2</sub> '	φD <sub>3</sub> '
3/4 × 1/2	Rc3/4 × Rc1/2	29	30	20	5.4	20	6.8	29.5	34.9	33	24	29.1	27
1 × 1/2	Rc1 × Rc1/2	32	33	25	8.7	20	6.8	36.3	42.1	41	24	29.1	27
1 × 3/4	Rc1 × Rc3/4	34	35	25	8.7	20	5.4	36.3	42.1	41	29.5	34.9	33
1 1/4 × 1/2	Rc1 1/4 × Rc1/2	34	38	25	8.7	20	6.8	45	50.8	50	24	29.1	27
1 1/4 × 3/4	Rc1 1/4 × Rc3/4	38	40	25	8.7	20	5.4	45	50.8	50	29.5	34.9	33
1 1/4 × 1	Rc1 1/4 × Rc1	40	42	25	8.7	25	8.7	45	50.8	50	36.3	42.1	41
1 1/2 × 1/2	Rc1 1/2 × Rc1/2	35	42	25	8.7	20	6.8	51	56.7	56	24	29.1	27
1 1/2 × 3/4	Rc1 1/2 × Rc3/4	38	43	25	8.7	20	5.4	51	56.7	56	29.5	34.9	33
1 1/2 × 1	Rc1 1/2 × Rc1	41	45	25	8.7	25	8.7	51	56.7	56	36.3	42.1	41
1 1/2 × 1 1/4	Rc1 1/2 × Rc1 1/4	45	48	25	8.7	25	8.7	51	56.7	56	45	50.8	50
2 × 3/4	Rc2 × Rc3/4	41	49	26	8.9	20	5.4	62.7	68.1	69	29.5	34.9	33
2 × 1	Rc2 × Rc1	44	51	26	8.9	25	8.7	62.7	68.1	69	36.3	42.1	41
2 × 1 1/4	Rc2 × Rc1 1/4	48	54	26	8.9	25	8.7	62.7	68.1	69	45	50.8	50
2 × 1 1/2	Rc2 × Rc1 1/2	52	55	26	8.9	25	8.7	62.7	68.1	69	51	56.7	56

備考

- 1) 樹脂被覆色 アイボリー色
- 2) 樹脂被覆色 淡緑色
- 3) ◇を除く寸法は参考寸法です

品名	外面樹脂被覆継手 PC継手 (ねじ込み式) 径違いチー		
略号	アイボリー色：RT 淡緑色：RT-G	年月日	2023-1-4
	株式会社プロテリアル 桑名工場	図番	G16-25038